

Patent Application
Docket #34645-00525USPT

Assistant Commissioner
for Patents
Washington, D.C. 20231

CERTIFICATE OF MAILING BY EXPRESS MAIL	
"EXPRESS MAIL" Mailing Label No. EL749033445US	
Date of Deposit: March 21, 2001	
I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231	
Type of Print Name	CAROL MARSTALLER
Signature	<i>Carol Marstaller</i>

COMMUNICATION SYSTEM AND METHOD FOR SHARED CONTEXT
COMPRESSION

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This patent application is related to and claims
priority from U.S. Patent Application No. 60/249,497, filed
10 November 16, 2000 (Attorney Docket No. 34645-525USPL); U.S.
Patent Application No. --/---,---, filed concurrently
herewith, entitled "Static Information Knowledge Used With
Binary Compression Method" (Attorney Docket No. 34645-
522USPT); U.S. Patent Application No. --/---,---, filed
15 concurrently herewith, entitled "Communication System and
Method Utilizing Request-Reply Communication Patterns For

5 Data Compression" (Attorney Docket No. 34645-523USPT); and
and U.S. Patent Application No. --/---,---, filed
concurrently herewith, entitled "System and Method For
Communicating With Temporary Compression Tables" (Attorney
Docket No. 34645-524USPT).

BACKGROUND OF THE INVENTION

Technical Field of the Invention

10 The present invention relates to the compression of
messages in communications using data protocols, e.g.
Internet protocols.

Background and Objects of the Present Invention

15 Two communication technologies that have become widely
used by the general public in recent years are cellular
telephony and the Internet. Some of the benefits that have
been provided by cellular telephony have been freedom of
mobility and accessability with reasonable service quality
20 despite a user's location. Until recently the main service
provided by cellular telephony has been speech. In contrast,
the Internet, while offering flexibility for different types
of usage, has been mainly focused on fixed connections and

large terminals. However, the experienced quality of some services, such as Internet telephony, has generally been regarded as quite low.

5 A number of Internet Protocols (IPs) have been developed to provide for communication across the Internet and other networks. Still another example of such an Internet protocol is the Session Initiation Protocol (SIP), which is an application layer protocol for establishing, modifying, and terminating multimedia sessions or calls. These sessions may
10 include Internet multimedia conferences, Internet telephony, and similar applications. As is understood in the art, SIP can be used over either the Transmission Control Protocol (TCP) or the User Datagram Protocol (UDP).

15 Another example of an Internet Protocol is the Real Time Streaming Protocol (RTSP), which is an application level protocol for control of the delivery of data with real-time properties, such as audio and video data. RTSP may also be used with UDP, TCP, or other protocols as a transport protocol. Still another example of an Internet Protocol is
20 the Session Description Protocol (SDP), which is used to advertise multimedia conferences and communicate conference

addresses and conference tool-specific information. SDP is also used for general real-time multimedia session description purposes. SDP is carried in the message body of SIP and RTSP messages. SIP, RTSP, and SDP are all ASCII text based using the ISO 10646 character set in UTF-8 encoding.

Due to new technological developments, Internet and cellular telephony technologies are beginning to merge. Future cellular devices will contain an Internet Protocol (IP) stack and support voice over IP as well as web-browsing, e-mail, and other desirable services. In an "all-IP" or "IP all the way" implementation, Internet Protocols are used end-to-end in the communication system. In a cellular system this may include IP over cellular links and radio hops. Internet Protocols may be used for all types of traffic including user data, voice or streaming data, and control data, such as SIP or RTSP data. Such a merging of technologies provides for the flexibility advantages of IP along with the mobility advantages of cellular technology.

As is understood in the art, the SIP, RTSP, and SDP protocols share similar characteristics which have implications in their use with cellular radio access. One

of these similarities is the general request and reply nature of the protocols. Typically, when a sender sends a request, the sender stays idle until a response is received. Another similarity, as previously described, is that SIP, RTSP, and SDP are all ASCII text based using the ISO 10646 character set with UTF-8 encoding. As a result, information is usually represented using a greater number of bits than would be required in a binary representation of the same information. Still another characteristic that is shared by the protocols is that they are generally large in size in order to provide the necessary information to session participants.

A disadvantage with IP is the relatively large overhead the IP protocol suite introduces due to large headers and text-based signaling protocols. It is very important in cellular systems to use the scarce radio resources in an efficient manner. In cellular systems it is important to support a sufficient number of users per cell, otherwise implementation and operation costs will be prohibitive. Frequency spectrum, and thus bandwidth, is a costly resource in cellular links and should be used efficiently to maximize system resources.

5 In the UMTS and EDGE mobile communication systems and
in future releases of second generation systems, such as GSM
and IS-95, much of the signaling traffic will be performed
by using Internet protocols. However as discussed, most of
10 the Internet protocols have been developed for fixed,
relatively broadband connections. When access occurs over
narrow band cellular links, compression of the protocol
messages is needed to meet quality of service requirements
such as set-up time and delay. Typically, compression over
15 the entire communication path is not needed. However,
compression of traffic over the radio link, such as from a
wireless user terminal to a core network, is greatly
desirable.

Standard binary compression methods, such as Lempel-Ziv
15 and Huffman coding, are very general in the sense that they
do not utilize any explicit knowledge of the structure of the
data to be compressed. The use of such methods on Internet
data protocols, e.g., SIP and RTSP, present difficulties for
the efficient compression of communication messages.
20 Standard binary compression methods available today are
typically designed for large data files. As a consequence,

use of such methods for the compression of small messages or messages with few repeated strings results in compression performance generally regarded as very poor. In fact, if the message to be compressed is small and/or contains few repeated strings, the use of some standard compression methods may result in a compressed packet which is actually larger than the original uncompressed packet, thereby achieving a counterproductive result.

One method for implementing a binary compression scheme is the use of dictionary based compression techniques. In general, a dictionary compression scheme uses a data structure known as a dictionary to store strings of symbols which are found in the input data. The scheme reads in input data and looks for strings of symbols which match those in the dictionary. If a string match is found, a pointer or index to the location of that string in the dictionary is output and transmitted instead of the string itself. If the index is smaller than the string it replaces, compression will occur. A decompressor contains a representation of the compressor dictionary, so that the original string may be reproduced from the received index. An example of a

dictionary compression method is the Lempel-Ziv (LZ77) algorithm. This algorithm operates by replacing character strings which have previously occurred in the file by references to the previous occurrence. This method is, of course, particularly successful in files where repeated strings are common.

Dictionary compression schemes may be generally categorized as either static or dynamic. A static dictionary is a predefined dictionary, which is constructed before compression occurs, and which does not change during the compression process. Static dictionaries are typically either stored in the compressor and decompressor prior to use, or transmitted and stored in memory prior to the start of compression operations.

A dynamic or adaptive dictionary scheme, on the other hand, allows the contents of the dictionary to change as compression occurs. In general, a dynamic dictionary scheme starts out with either no dictionary or a default, predefined dictionary and adds new strings to the dictionary during the compression process. If a string of input data is not found in the dictionary, the string is added to the dictionary in

One method of dictionary compression is of the type known as sliding window compression. In this method the compressor moves a fixed-size sliding window from left to right through the file during compression. The compression algorithm searches the file to the left of the window for matches to strings currently in the window. If a match is found the string is replaced by a reference to the location of the match within the file along with a reference to the length of the match. Alternately, the window may be a text

windown of a large block of recently decoded text and a look-ahead buffer. In this version, the look-ahead buffer is used to search for matches within the text window. If a match is found the string is replaced by a reference to the location of the match within the text window and reference to the length of the match. This information is used by the decompressor which maintains the same dictionary to reproduce the original information.

Another method for the compression of data is the use of a binary code tree. In a binary code tree, symbols or strings which are to be compressed are represented in a tree structure by a variable number of bits such that each symbol is uniquely decodable. Typically, symbols with higher probabilities of occurrence in the input data are represented by a shorter number of bits than those which have lower probabilities of occurrence. In the construction of the binary code tree, individual symbols are laid out as a string of leaf nodes connected to a binary tree. Symbols with higher probabilities of occurrence are represented as shorter branches of the tree resulting in a fewer number of bits being required to represent them. Conversely, symbols with

lower probabilities of occurrence are represented as longer branches of the tree requiring a greater number of representation bits. When a string of input data matches a symbol in the binary code tree of the compressor, the code
5 of the symbol is transmitted instead of the symbol itself resulting in data compression. A decompressor receiving the code reconstructs the original symbol or string using an identical binary code tree.

Similarly to dictionary compression, binary code trees
10 may be static or dynamic. In a static binary code tree scheme, a predefined binary code tree is constructed prior to compression and does not change during the compression process. As with static dictionaries, static binary code trees may be stored in the compressor and decompressor in
15 advance, or transmitted and stored prior to the start of compression.

A dynamic or adaptive binary code tree allows for the addition of new symbols or strings to the code tree during the compression process. Various methods may be used to
20 update the nodes of the tree according to the type of binary code tree compression used to allow for the addition of new

symbols and the rearrangement of the code tree. The binary code tree in the decompressor must also be updated according to the same rules as the binary code tree in the compressor.

One example of a binary code tree compression scheme is that of a Huffman coding compression scheme. Huffman compression is a general compression method intended primarily for compression of ASCII files. Characters occurring frequently in the files are replaced by shorter codes, i.e. codes with less than the 8 bits used by the ASCII code. Huffman compression can be successful in files where relatively few characters are used.

A general criteria for successful compression using the aforementioned binary compression algorithms is that the file to be compressed is reasonably large. The codes for Huffman compression must not be too large compared to the file which is being compressed. For standard Lempel-Ziv compression, the file to be compressed must be large enough to have many repeated strings to achieve efficient compression. The messages produced by the aforementioned protocols are mostly a few hundred bytes and not large enough to allow efficient

compression with the aforementioned algorithms on a message by message basis.

One technique for compressing communication messages is that of header compression. Header compression is used to reduce the size of a communication message or packet by removing or reducing the size of header fields within the communication message. Header compression relies on many fields of a header remaining constant or changing very little in consecutive packets belonging to the same packet stream. Fields that do not change between packets do not need to be transmitted at all, whereas fields that change often with small and/or predictable values can be encoded incrementally so that the number of bits needed for these fields may be significantly decreased. Only fields that change often and randomly, such as checksums or authentication data, need to be transmitted in every header. Header compression is performed in such a way that a decompressor can reconstruct the header if its context state is identical to the context state used when compressing the header.

In header compression techniques, the context state is the state which a compressor uses to compress a header and

a decompressor uses to decompress a compressed header. The context contains relevant information from the current and previous headers in the current packet stream, such as static fields and possible reference values for compression and decompression. Additional information describing the packet stream, such as information about how the IP identifier field changes and the typical inter-packet increase in sequence numbers or timestamps, may also be part of the context.

The context may include both a static and dynamic part.

10 The static part includes static fields that are expected to be constant throughout the lifetime of the packet stream. Examples of static fields within an Internet Protocol Version 6 (IPv6) header include the IP (Internet Protocol) version field, flow label field, payload length field, next header field, source IP address, and destination IP address. The dynamic part includes fields within the header which are expected to vary within the packet stream. Examples of dynamic IPv6 header fields include the traffic class field and the hop limit field.

20 Examples of static header fields within an Internet
Protocol Version 4 (IPv4) packet stream include the IP

version field, the protocol field, the source IP address, and the destination IP address. Examples of dynamic header fields within an IPv4 packet stream include the type-of-service field, the time-to-live field, and the identification field. Examples of static UDP (User Datagram Protocol) header fields include the source port field and the destination port field. An example of a static field within a RTP (Real-time Transport Protocol) header includes the sending source (SSRC) field.

10 The aforescribed packet stream is a sequence of packets whose headers are similar and share context information, such as a common source and destination address. The context information for a packet stream is associated with a context identifier (CID). The context identifier
15 (CID) is a small unique number identifying the context that should be used to decompress a compressed header within the packet stream. The context information is conceptually stored in a table which is indexed using the context identifier (CID). The context identifier (CID) is carried
20 in both full headers and compressed headers during the transmission of communication messages.

10

15

20

information between a compressor and decompressor at each communication entity in a communication system. As a result, context information will be shared for each channel pair. In another aspect of the present invention, multiple communication sessions between communication entities may share the same context information for the compression and decompression of communication messages.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the system, method and apparatus of the present invention may be had by reference to the following Detailed Description when taken in conjunction with the accompanying Drawings wherein:

FIGURE 1 illustrates an exemplary system for communication in accordance with the present invention;

FIGURE 2 illustrates an exemplary embodiment for sharing context information in accordance with the present invention;

FIGURE 3 illustrates an exemplary methodology of updating context information in accordance with the present invention; and

FIGURE 4 illustrates another exemplary embodiment for sharing context information in accordance with the present invention.

5 **DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EXEMPLARY EMBODIMENTS**

60 THE PRESENT INVENTION
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150
2160
2170
2180
2190
2200
2210
2220
2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
2610
2620
2630
2640
2650
2660
2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100
3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260
5270
5280
5290
5300
5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
5490
5500
5510
5520
5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
6780
6790
6800
6810
6820
6830
6840
6850
6860
6870
6880
6890
6900
6910
6920
6930
6940
6950
6960
6970
6980
6990
7000
7010
7020
7030
7040
7050
7060
7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170
7180
7190
7200
7210
7220
7230
7240
7250
7260
7270
7280
7290
7300
7310
7320
7330
7340
7350
7360
7370
7380
7390
7400
7410
7420
7430
7440
7450
7460
7470
7480
7490
7500
7510
7520
7530
7540
7550
7560
7570
7580
7590
7600
7610
7620
7630
7640
7650
7660
7670
7680
7690
7700
7710
7720
7730
7740
7750
7760
7770
7780
7790
7800
7810
7820
7830
7840
7850
7860
7870
7880
7890
7900
7910
7920
7930
7940
7950
7960
7970
7980
7990
8000
8010
8020
8030
8040
8050
8060
8070
8080
8090
8100
8110
8120
8130
8140
8150
8160
8170
8180
8190
8200
8210
8220
8230
8240
8250
8260
8270
8280
8290
8300
8310
8320
8330
8340
8350
8360
8370
8380
8390
8400
8410
8420
8430
8440
8450
8460
8470
8480
8490
8500
8510
8520
8530
8540
8550
8560
8570
8580
8590
8600
8610
8620
8630
8640
8650
8660
8670
8680
8690
8700
8710
8720
8730
8740
8750
8760
8770
8780
8790
8800
8810
8820
8830
8840
8850
8860
8870
8880
8890
8900
8910
8920
8930
8940
8950
8960
8970
8980
8990
9000
9010
9020
9030
9040
9050
9060
9070
9080
9090
9100
9110
9120
9130
9140
9150
9160
9170
9180
9190
9200
9210
9220
9230
9240
9250
9260
9270
9280
9290
9300
9310
9320
9330
9340
9350
9360
9370
9380
9390
9400
9410
9420
9430
9440
9450
9460
9470
9480
9490
9500
9510
9520
9530
9540
9550
9560
9570
9580
9590
9600
9610
9620
9630
9640
9650
9660
9670
9680
9690
9700
9710
9720
9730
9740
9750
9760
9770
9780
9790
9800
9810
9820
9830
9840
9850
9860
9870
9880
9890
9900
9910
9920
9930
9940
9950
9960
9970
9980
9990
10000
10010
10020
10030
10040
10050
10060
10070
10080
10090
10100
10110
10120
10130
10140
10150
10160
10170
10180
10190
10200
10210
10220
10230
10240
10250
10260
10270
10280
10290
10300
10310
10320
10330
10340
10350
10360
10370
10380
10390
10400
10410
10420
10430
10440
10450
10460
10470
10480
10490
10500
10510
10520
10530
10540
10550
10560
10570
10580
10590
10600
10610
10620
10630
10640
10650
10660
10670
10680
10690
10700
10710
10720
10730
10740
10750
10760
10770
10780
10790
10800
10810
10820
10830
10840
10850
10860
10870
10880
10890
10900
10910
10920
10930
10940
10950
10960
10970
10980
10990
11000
11010
11020
11030
11040
11050
11060
11070
11080
11090
11100
11110
11120
11130
11140
11150
11160
11170
11180
11190
11200
11210
11220
11230
11240
11250
11260
11270
11280
11290
11300
11310
11320
11330
11340
11350
11360
11370
11380
11390
11400
11410
11420
11430
11440
11450
11460
11470
11480
11490
11500
11510
11520
11530
11540
11550
11560
11570
11580
11590
11600
11610
11620
11630
11640
11650
11660
11670
11680
11690
11700
11710
11720
11730
11740
11750
11760
11770
11780
11790
11800
11810
11820
11830
11840
11850
11860
11870
11880
11890
11900
11910
11920
11930
11940
11950
11960
11970
11980
11990
12000
12010
12020
12030
12040
12050
12060
12070
12080
12090
12100
12110
12120
12130
12140
12150
12160
12170
12180
12190
12200
12210
12220
12230
12240
12250
12260
12270
12280
12290
12300
12310
12320
12330
12340
12350
12360
12370
12380
12390
12400
12410
12420
12430
12440
12450
12460
12470
12480
12490
12500
12510
12520
12530
12540
12550
12560
12570
12580
12590
12600
12610
12620
12630
12640
12650
12660
12670
12680
12690
12700
12710
12720
12730
12740
12750
12760
12770
12780
12790
12800
12810
12820
12830
12840
12850
12860
12870
12880
12890
12900
12910
12920
12930
12940
12950
12960
12970
12980
12990
13000
13010
13020
13030
13040
13050
13060
13070
13080
13090
13100
13110
13120
13130
13140
13150
13160
13170
13180
13190
13200
13210
13220
13230
13240
13250
13260
13270
13280
13290
13300
13310
13320
13330
13340
13350
13360
13370
13380
13390
13400
13410
13420
13430
13440
13450
13460
13470
13480
13490
13500
13510
13520
13530
13540
13550
13560
13570
13580
13590
13600
13610
13620
13630
13640
13650
13660
13670
13680
13690
13700
13710
13720
13730
13740
13750
13760
13770
13780
13790
13800
13810
13820
13830
13840
13850
13860
13870
13880
13890
13900
13910
13920
13930
13940
13950
13960
13970
13980
13990
14000
14010
14020
14030
14040
14050
14060
14070
14080
14090
14100
14110
14120
14130
14140
14150
14160
14170
14180
14190
14200
14210
14220
14230
14240
14250
14260
14270
14280
14290
14300
14310
14320
14330
14340
14350
14360
14370
14380
14390
14400
14410
14420
14430
14440
14450
14460
14470
14480
14490
14500
14510
14520
14530
14540
14550
14560
14570
14580
14590
14600
14610
14620
14630
14640
14650
14660
14670
14680
14690
14700
14710
14720
14730
14740
14750
14760
14770
14780
14790
14800
14810
14820
14830
14840
14850
14860
14870
14880
14890
14900
14910
14920
14930
14940
14950
14960
14970
14980
14990
15000
15010
15020
15030
15040
15050
15060
15070
15080
15090
15100
15110
15120
15130
15140
15150
15160
15170
15180
15190
15200
15210
15220
15230
15240
15250
15260
15270
15280
15290
15300
15310
15320
15330
15340
15350
15360
15370
15380
15390
15400
15410
15420
15430
15440
15450
15460
15470
15480
15490
15500
15510
15520
15530
15540
15550
15560
15570
15580
15590
15600
15610
15620
15630
15640
15650
15660
15670
15680
15690
15700
15710
15720
15730
15740
15750
15760
15770
15780
15790
15800
15810
15820
15830
15840
15850
15860
15870
15880
15890
15900
15910
15920
15930
15940
15950
15960
15970
15980
15990
16000
16010
16020
16030
16040
16050
16060
16070
16080
16090
16100
16110
16120
16130
16140
16150
16160
16170
16180
16190
16200
16210
16220
16230
16240
16250
16260
16270
16280
16290
16300
16310
16320
16330
16340
16350
16360
16370
16380
16390
16400
16410
16420
16430
16440
16450
16460
16470
16480
16490
16500
16510
16520
16530
16540
16550
16560
16570
16580
16590
16600
16610
16620
16630
16640
16650
16660
16670
16680
16690
16700
16710
16720
16730
16740
16750
16760
16770
16780
16790
16800
16810
16820
16830
16840
16850
16860
16870
16880
16890
16900
16910
16920
16930
16940
16950
16960
16970
16980
16990
17000
17010
17020
17030
17040
17050
17060
17070
17080
17090
17100
17110
17120
17130
17140
17150
17160
17170
17180
17190
17200
17210
17220
17230
17240
17250
17260
17270
17280
17290
17300
17310
17320
17330
17340
17350
17360
17370
17380
17390
17400
17410
17420
17430
17440
17450
17460
17470
17480
17490
17500
17510
17520
17530
17540
17550
17560
17570
17580
17590
17600
17610
17620
17630
17640
17650
17660
17670
17680
17690
17700
17710
17720
17730
17740
17750
17760
17770
17780
17790
17800
17810
17820
17830
17840
17850
17860
17870
17880
17890
17900
17910
17920
17930
17940
17950
17960
17970
17980
17990
18000
18010
18020
18030
18040
18050
18060
18070
18080
18090
18100
18110
18120
18130
18140
18150
18160
18170
18180
18190
18200
18210
18220
18230
18240
18250
18260
18270
18280
18290
18300
18310
18320
18330
18340
18350
18360
18370
18380
18390
18400
18410
18420
18430
18440
18450
18460
18470
18480
18490
18500
18510
18520
18530
18540
18550
18560
18570
18580
18590
18600
18610
18620
18630
18640
18650
18660
18670
18680
18690
18700
18710
18720
18730
18740
18750
18760
18770
18780
18790
18800
18810
18820
18830
18840
18850
18860
18870
18880
18890
18900
18910
18920
18930
18940
18950
18960
18970
18980
18990
19000
19010
190

a link 125. Fixed network 130 is in communication with a base station 140 via a link 135. Base station 140 is in communication with a terminal 150, which may be a mobile terminal or a fixed terminal, using communication link 145.

5 According to an embodiment of the present invention, the mobile terminal 110 communicates with the base station 120 using compressed messages with associated context information, using a compression methodology such as using a header compression scheme or a binary compression scheme,
10 over the communication link 115. Similarly, base station 140 may communicate with terminal 150 using compressed messages with associated context information. It should be understood that components in the system of FIGURE 1, such as mobile terminal 110 and base station 140, may include a memory 160
15 and processor 155 used for storing and executing software instructions which implement compression and decompression algorithms. It should also be understood that the present invention may be used in other communication systems, such as a cellular network, that use communication protocols
20 having context information over links in which compression is desired.

FIGURE 2 illustrates an exemplary embodiment for sharing context information in accordance with the present invention. In this embodiment, an entity A (210) is in communication with an entity B (230) using communication links (250, 255) with a communication protocol in which data compression is used. According to the exemplary embodiment, communication links 250 and 255 comprise a channel pair. As illustrated in FIGURE 2, entity A (210) includes a compressor 215 for compressing messages to be transmitted to entity B (230) over communication link 250, and a decompressor 225 for decompressing data received from entity B (230) over communication link 255. In addition, entity A (210) includes a context table 220, associated with compressor 215 and decompressor 225, for storing context information. It should be understood that the compressor and/or decompressor may be implemented using a processor and associated memory having stored therein instructions for a compression/decompression algorithm(s). It should also be understood that the communication entities may comprise a number of communication devices. For example, entity A (210) may comprise a mobile terminal, and entity B (230) may comprise a base station.

As further illustrated in FIGURE 2, entity B (230) includes a decompressor 235 for decompressing messages received from communication link 250, and a compressor 245 for compressing messages to be transmitted over communication link 255. Entity B (230) also contains a context table 240, associated with decompressor 235 and compressor 245, for storing context information.

During operation, compressor 215 and decompressor 225 of entity A (210) share the same context table 220. The context table includes context information which is used for both the compression and decompression of communication messages sent and received over the channel pair (250,255). Similarly, decompressor 235 and compressor 245 of entity B (230) share the same context table 240, which is shared for both the decompression and compression of communication messages.

Thus, instead of having a separate context for each communication channel, the exemplary embodiment in accordance with the present invention provides for a shared context for each channel pair. By sharing the context table between the compressor and decompressor at each entity, both the

compressor and decompressor at each entity are able to update the context information in the context table from both sent and received communication messages. Because context information in both sent messages and received messages is
5 used to update the context information, the compression efficiency may be increased.

In accordance with an embodiment of the present invention, the context information stored in a context table may include any information needed to compress and decompress
10 communication messages. For field compression techniques, such as the aforescribed header compression techniques, the context information may include specific fields contained in the communication message. For binary compression techniques, such as that of dictionary compression, the
15 context may include the dictionaries or tables used by the method. For example, the context information may include messages or parts of messages which would be useful to save in dictionaries for use during compression and decompression.

In FIGURE 3 is illustrated an exemplary method of
20 updating context information in accordance with the present invention. In the exemplary illustration of FIGURE 3, flow

arrows indicate the message flow (M1-M4) between entity A (210) and entity B (230) during an exemplary communication session. In the exemplary illustration, each of communication messages M1-M4 contain new context information which is desired to be stored in the context tables of each communication entity. The context table columns indicate the contents of entity A's context table (220) and entity B's context table (240) at given instances during the communication session. The notation of "E" represents an empty context within the context table, while the notation "Mn" represents the context information of message Mn as being stored in the context table. The notations of C(Mn) and DC(Mn) represent the respective compression and decompression of message Mn using the context information located in the current context table.

In this exemplary illustration, entity A (210) and entity B (230) begin with context tables (220,240) containing empty context information, "E", prior to the start of the communication session. Entity A (210) prepares to send a first communication message, M1, to entity B (230). The context information, "M1", related to message M1 is added to

context table 220 (step 305). Message M1 is then compressed using the context information, "M1", from context table 220 (step 310). Entity A (210) then sends the compressed message M1, which includes the context information, "M1", associated with message M1, to entity B (230) (step 315). After receiving the compressed message M1, entity B (230) decompresses compressed message M1 using the "M1" context information (step 320). Entity B (230) then adds the "M1" context information to its context table 240 (step 325).

10 When entity B (230) prepares to send a communication message M2, to entity A (210), entity B (230) adds the context information, "M2", related to message M2 to the context table 240 (step 330). As a result, context table 240 will now contain the "M1,M2" context information. Message
15 M2 is then compressed using the context information, "M1,M2", from context table 240 (step 335). After compression, entity B (230), sends the compressed message M2, which includes the context information, "M2", associated with message M2, to entity A (210) (step 340). After receiving the compressed
20 message M2, entity A (210) decompresses compressed message M2 using the "M1,M2" context information (step 345). Entity

A (210) then adds the "M2" context information to its context table 220 (step 350), so that context table 220 now contains context information "M1,M2".

Further communication between entity A (210) and entity
5 B (230) are performed in the same manner. For example,
entity A (210) prepares to send another communication message
M3 to entity B (230) by first adding the context information,
"M3", related to message M3 to the context table 220 (step
355). Message M3 is then compressed using the context
10 information, "M1,M2,M3", from context table 220 (step 360).
Entity A (210) then sends the compressed message M3, which
includes the context information, "M3", associated with
message M3, to entity B (230) (step 365). After receiving
the compressed message M3, entity B (230) decompresses
15 compressed message M3 using the "M1,M2,M3" context
information (step 370). Entity B (230) then adds the "M3"
context information to its context table 240 (step 375).

When entity B (230) sends another communication message
M4 to entity A (210), entity B (230) adds the context
20 information, "M4", related to message M4 to the context table
240 (step 380). As a result, context table 240 will now

contain the "M1,M2,M3,M4" context information. Message M4
is then compressed using the context information,
"M1,M2,M3,M4", from context table 240 (step 385). After
compression, entity B (230), sends the compressed message M4,
5 which includes the context information, "M4", associated with
message M4, to entity A (210) (step 390). After receiving
the compressed message M4, entity A (210) decompresses
compressed message M4 using the "M1,M2,M3,M4" context
information (step 395). Entity A (210) then adds the "M4"
10 context information to its context table 220 (step 397), so
that context table 220 now contains context information
"M1,M2,M3,M4".

As should be understood by the foregoing description,
both communication entities maintain identically updated
15 context tables for compression and decompression of
communication messages. When communication messages are
transmitted which contain the same context information as
that of a previous message which has been stored in the
context table, a context identifier may be substituted for
20 the context information by the compressor to generate the
compressed message. As a result, a decompressor may use the

context identifier to decompress the message using the same context information.

FIGURE 4 illustrates another exemplary embodiment for sharing context information in accordance with the present invention. In this embodiment an entity A (410) communicates with an entity B (430) using a number of communication sessions (450a,...,450n) with a communication protocol. Entity A (410) sends communication messages which have been compressed using context information to entity B (430). As illustrated in FIGURE 4, entity A (410) includes a compressor 415 for compressing messages to be transmitted to entity B (430) using communication sessions (450a,...,450n). In addition, entity A (410) contains a context table 420 associated with compressor 415. The context table 420 includes context information used for the compression of messages which are sent using communication sessions (450a,...,450n). Again, it should be understood that the communication entities may be a number of communication devices. For example, entity A (410) may comprise a mobile terminal, and entity B (430) may comprise a base station.

As further illustrated in FIGURE 4, entity B (430) contains a decompressor 235 for decompressing communication messages received from entity A (410) using communication sessions (250a,...250n). In addition, entity B (430) contains a context table 440 associated with decompressor 235. Context table 440 includes context information associated with the compressed messages which are sent using communication sessions (450a,...,450n) so that the same context information that was used to compress the communication messages can be used to decompress them.

During operation, compressor 415 of entity A (410) uses context table 420 for compression of the messages to be sent to entity B (430) over communication sessions (450a,...,450n). Decompressor 435 of entity B (430) uses context table 440 for decompression of the compressed messages received from entity A (410) over communication sessions (450a,...,450n). Instead of having one context for each communication session, the exemplary embodiment of FIGURE 4 allows the same context information to be shared among multiple sessions, resulting in greater compression efficiency. For example, it may be necessary to send context

information only once for one of the communication sessions,
while the same context information may be used for the
compression and decompression of messages for all of the
communication sessions. Examples of context information
5 which may be shared among multiple communication sessions
between entity A (410) and entity B (430) include the IP-
destination address, the IP-source address, the IP-version
number, etc.

It should be understood that various modifications and
10 additions may be made in accordance with embodiments of the
present invention. For example, in the case in which there
is more than one logical link between communication entities,
it may be necessary to identify which channels are associated
with one another and share a context. An example of channels
15 which may need to be associated with one another to share
context information are request and response channels. Such
an identification may be achieved through the use of channel
mapping. One methodology of implementing channel mapping may
be achieved by assigning an identifier for each channel pair.
20 The channel pair identifier may then be included in each
communication packet which is sent over associated

communication channels. It should be understood that an identifier may also be used to associate any number of channels or sessions with one another in a communication session.

- 5 Although various embodiments of the method, system, and apparatus of the present invention have been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiments disclosed, but
- 10 is capable of numerous rearrangements, modifications and substitutions without departing from the scope of the invention as set forth and defined by the following claims.